



**PC-2000
SUBWOOFER**

PC-2000 – SUPERIOR CYLINDER PERFORMANCE, SOUNDPATH ISOLATION

The original SVS subwoofer was a cylinder design, and this unique and elegant form factor has since become an iconic symbol of SVS performance heritage. The PC-2000 is our most affordable powered cylinder, but after experiencing its performance, no one would dare call it 'entry level'. Every component reflects SVS performance pedigree, and the PC-2000 obliterates over-priced and under-performing brick & mortar subwoofers, even at twice the price. It's also the first subwoofer to come standard with the SVS SoundPath Subwoofer Isolation System, which decouples and isolates the PC-2000 from the flooring, resulting in tighter and cleaner sounding bass, less buzz/ rattle in the room, and fewer complaints from adjacent neighbors in apartments and townhouses.

SPECIFICATION

- » New, down-firing SVS 12" 2000-series driver
- » New Sledge STA-500D DSP amplifier, 500 watts RMS (1100 watts peak dynamic)
- » Interchangeable top cap in Premium Black Ash and Piano Gloss Black
- » Rear-firing 4" high-flow port with large radius inner and outer flanges
- » High-grade black fabric exterior cover
- » Extremely rigid and strong cylinder enclosure
- » 17-270 Hz +/- 3 dB
- » Dims: 34" (H), 16-5/8" (OD)
- » Weight: 50 pounds

COMPACT FOOTPRINT, PREMIUM FINISH VERSATILITY

With only a 16.5" diameter footprint, the PC-2000 will fit into almost any location, and no other subwoofer design offers more bass performance per square inch of floor space. Using vertical height to achieve a generous enclosure volume and a deep-tuned port, the result is excellent deep bass performance and outstanding mid-bass slam – all in a very manageable size. The all new integrated, interchangeable top cap ensures that the PC-2000 will fit into any décor.



SVS 12" HIGH OUTPUT DRIVER

Designed from scratch—and optimized to through exhaustive testing until it delivered unprecedented performance we were after—the all-new 2000-series driver does us proud.

- » FEA-optimized motor technology for low distortion.
- » Heavy-duty 2" voice coil for extreme power handling.
- » Upgraded Nomex spider for improved linearity and driver control at extreme drive levels.

NEW SLEDGE AMPLIFIER STA-500D: PRECISE, FLEXIBLE, POWERFUL

- » 500 watts RMS continuous (1100 watts peak dynamic), Class D power with 'green' (<0.5 watts consumption) standby mode.
- » DSP control for accurate response and refined behavior under all operating conditions.
- » Stereo line-level RCA Input & 80Hz High Pass Filtered Output connections.
- » 3-12V trigger with 1/8" (3.5 mm) TRS mini-jack input.
- » Continuously variable low pass filter frequency with disable/LFE setting.
- » Continuously variable volume and phase controls.

SVS

